



FOOT Ø40 M8 H68+3

J0150	FOOT Ø40 M8 H68+3
MATERIAL	black PA shell galvanized steel stem non-slip synthetic rubber disk
COMMERCIAL INFO	A2 stainless steel stem in pack of 4 pcs on demand
USAGE NOTES	max static load 10000 N




FOOT Ø40 M8 H93+3

J0170	FOOT Ø40 M8 H93+3
MATERIAL	black PA shell galvanized steel stem non-slip synthetic rubber disk
COMMERCIAL INFO	A2 stainless steel stem in pack of 4 pcs on demand
USAGE NOTES	max static load 10000 N




FOOT Ø40 M10 H68+3

J0200	FOOT Ø40 M10 H68+3
MATERIAL	black PA shell galvanized steel stem non-slip synthetic rubber disk
COMMERCIAL INFO	A2 stainless steel stem in pack of 4 pcs on demand
USAGE NOTES	max static load 10000 N




FOOT Ø40 M10 H93+3

J0250	FOOT Ø40 M10 H93+3
MATERIAL	black PA shell galvanized steel stem non-slip synthetic rubber disk
COMMERCIAL INFO	A2 stainless steel stem in pack of 4 pcs on demand
USAGE NOTES	max static load 10000 N




FOOT Ø40 M10 H123+3

J0300	FOOT Ø40 M10 H123+3
MATERIAL	black PA shell galvanized steel stem non-slip synthetic rubber disk
COMMERCIAL INFO	A2 stainless steel stem in pack of 4 pcs on demand
USAGE NOTES	max static load 10000 N




FOOT Ø40 M16 H93+3

J0350	FOOT Ø40 M16 H93+3
MATERIAL	black PA shell galvanized steel stem non-slip synthetic rubber disk
COMMERCIAL INFO	A2 stainless steel stem in pack of 4 pcs on demand
USAGE NOTES	max static load 10000 N



FOOT Ø40 M16 H133+3

J0400	FOOT Ø40 M16 H133+3
MATERIAL	black PA shell galvanized steel stem non-slip synthetic rubber disk
COMMERCIAL INFO	A2 stainless steel stem in pack of 4 pcs on demand
USAGE NOTES	max static load 10000 N



FOOT Ø40 M16 H173+3

J0450	FOOT Ø40 M16 H173+3
MATERIAL	black PA shell galvanized steel stem non-slip synthetic rubber disk
COMMERCIAL INFO	A2 stainless steel stem in pack of 4 pcs on demand
USAGE NOTES	max static load 10000 N

